

## ELECTRICAL PERFORMANCE AT STC<sup>1</sup>

			FLEX-03 110N	FLEX-03 115N	FLEX-03 120N	FLEX-03 125N	FLEX-03 130N
Nominal Power	$P_{MPP}$	[W]	110	115	120	125	130
Aperture Efficiency	$\eta$	[%]	14.4%	15.0%	15.7%	16.4%	17.0%
Power Output Tolerance		[W]	+5/-0	+5/-0	+5/-0	+5/-0	+5/-0
Maximum Power Voltage	$V_{MPP}$	[V]	28.5	29.0	29.5	30.0	30.5
Maximum Power Current	$I_{MPP}$	[A]	3.87	3.97	4.07	4.16	4.26
Open Circuit Voltage	$V_{OC}$	[V]	36.5	36.8	37.1	37.4	37.7
Short Circuit Current	$I_{SC}$	[A]	4.70	4.70	4.70	4.70	4.70
Maximum Series Fuse Rating		[A]	10				
Maximum System Voltage	(IEC/UL)	[V]	1000/1000				

<sup>1</sup>Standard Test Conditions (STC): 1000 W/m<sup>2</sup>, 25°C cell temperature, AM 1.5 spectrum

## THERMAL CHARACTERISTICS

NOCT	[°C]	48
Temperature Coefficient of $P_{MPP}$	[%/°C]	-0.38
Temperature Coefficient of $V_{OC}$	[%/°C]	-0.28
Temperature Coefficient of $I_{SC}$	[%/°C]	0.008

## PHYSICAL AND MECHANICAL SPECIFICATIONS

Length	2585 mm (101.8 in)
Width	348 mm (13.7 in)
Thickness, Maximum at J-Box*, Module	17 mm (0.7 in), 2.5 mm (0.1 in)
Weight (Module without adhesive)	1.6 kg (3.6 lb)
Weight (Module with adhesive)	1.9 kg (4.3 lb)
Weight/Area (Module without adhesive)	1.8 kg/m <sup>2</sup> (0.4 lb/ft <sup>2</sup> )
Weight/Area (Module with adhesive)	2.2 kg/m <sup>2</sup> (0.5 lb/ft <sup>2</sup> )
Junction Box Type	IP68
Cable Connections	Amphenol Technology Shenzhen (E346053)
Cell Type	Copper Indium Gallium Diselenide (CIGS)
Warranty**	5 year workmanship; 10/25 year power output
Certifications	UL 1703, IEC 61646, IEC 61730, cUL 1703, IEC 62716, Australia CEC
Packaging Info	15 modules per crate, 150 modules per pallet, 600 modules per 20' ISO container, 2400 modules per 40' ISO container

\*25 mm (0.1 in) for the rest of the module with adhesive

\*\*1.6 mm (0.06 in) for the rest of module without adhesive

\*\*Please see full warranty for details

Made in the USA and China